(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 6 May 2005 (06.05.2005)

(10) International Publication Number WO 2005/039763 A1

(51) International Patent Classification⁷: 31/14, C08F 10/00

B01J 31/12,

(21) International Application Number:

PCT/EP2004/011316

(22) International Filing Date: 9 October 2004 (09.10.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

103 48 624.0

15 October 2003 (15.10.2003) DE

6 November 2003 (06.11.2003) 60/518,427

(71) Applicant (for all designated States except US): BASELL POLYOLEFINE GMBH [DE/DE]; Brühler Strasse 60, 50389 Wesseling (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MIHAN, Shahram [IR/DE]; Am Eichwald 18, 65812 Bad Soden (DE). ROSENDORFER, Philipp [DE/DE]; Dochnahlstrasse 30, 67434 Neustadt (DE). KARER, Rainer [DE/DE]; Oskar-Schlemmer-Ring 48, 67657 Kaiserslautern (DE). SCHNEIDER, Martin [DE/DE]; Hornauer Str. 37b, 65779 Kelkheim (DE). ECK, Peter [DE/DE]; Brunnengasse 4, 67098 Bad Dürkheim (DE).

(74) Common Representative: BASELL POLYOLEFINE GMBH; Intellectual Property, Industriepark Hoechst, Bldg E 413, 65926 Frankfurt am Main (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

65/79 Kelkheim (DE). ECK, Peter [DE/DE]; Brunnengassc 4, 67098 Bad Dürkheim (DE).

65/79 Kelkheim (DE).

65/79 to a finely divided, porous, mechanically stable and chemically inert support, has a proportion by weight of metal alkyl compound of at least 5% by weight, based on the support, and has an angle of repose, determined in accordance with ISO 4324, of up to 48°. The solid allows trouble-free metering as active component into a reactor.